

CS300® IABP UNIVERSAL TRANSPORT SYSTEM (UTS) A SIMPLE, SAFE AND VERSATILE SOLUTION.

CARDIOVASCULAR



SUMMARY OF FEATURES AND BENEFITS

- **The Big Wheel Assembly™** provides smooth maneuvering on uneven pathways and in inclement weather.
- **The Lightweight Docking Station Mount™** facilitates rapid securement of the pump to aircraft and ambulances.
- **Easy and Fast Pump Installation** for safe patient transport.



Step 1: Wheel CS300 to vehicle



Step 2: Install docking station



Step 3: Lock CS300 into Docking Station

Datascope Corp.
15 Law Drive
Fairfield, NJ 07004
Phone: 1 800 777 4222
+1 973 244 6100
Fax: 1 800 258 8762
+1 973 244 6279
www.datascope.com
www.maquet.com

TECHNICAL SPECIFICATIONS AND ORDERING INFORMATION

CS300® UTS with IntelliSense™	
Dimensions	30.0"H x 22.5"D x 13.2"W (76.2cm x 57.2cm x 33.5cm)
Console Weight	135.3 lbs. (61.4 Kg)
Lightweight Docking Station Mount (Suggested Option)	17.8" (45.1cm) x 20.0" (50.8cm)



UTS Ambulance Installation

CS300® UTS with IntelliSense™	Part Number
Used mainly for IABP assisted patient transport and does not include a hospital cart	
<ul style="list-style-type: none"> ■ Accessory storage case ■ CS300 UTS should be fastened to a docking station for mounting in vehicle or aircraft/helicopter ■ Standard accessories include: 5-Lead Fully Shielded ECG Patient Trunk Cable, 5-Lead Fully Shielded Leadwire Set (50"), 5-Lead ESIS Fully Shielded Leadwire Set (50"), External Signal Cables (2), 4 Wire RJ-11 Cable, External Low Level BP Cable, Manual Fill Kits (2), CS300 Operations Manual, CS300 Service Manual, Syringe, Helium Cylinder Washers, Thermal Recorder Chart Paper, Fiber Optic Cleaning Swabs, Fiber Optic Connector Cleaner, Safety Disk, Condensate Removal Module. 	
CS300 IABP - UTS, English United States, 110V	0998-00-3023-83
CS300 IABP - UTS, English International, 220V	0998-00-3023-85
CS300 IABP - UTS, Spanish, 110V	0998-00-3023-87
CS300 IABP - UTS, Spanish, 220V	0998-00-3023-88
CS300 IABP - UTS, German, 220V	0998-00-3023-91
CS300 IABP - UTS, French, 110V	0998-00-3023-92
CS300 IABP - UTS, French, 220V	0998-00-3023-94
CS300 IABP - UTS, Japanese, 110V	0998-00-3023-95
CS300 IABP - UTS, Italian, 220V	0998-00-3023-97
CS300 IABP - UTS, Portuguese, 220V	0998-00-3023-98
CS300 IABP - UTS, Portuguese, 110V	0998-00-3023-99
CS300 IABP - UTS, Swedish, 220V	0998-00-3023-73
CS300 IABP - UTS, Chinese, 220V	0998-00-3023-75



Lightweight Docking Station Mount

Lightweight Docking Station Mount**	0436-00-0110
<ul style="list-style-type: none"> ■ Ideal for 10 and 17 seat tracks ■ For use with air and ground vehicles ■ Includes two (2) locking shear pins and five (5) Ankra seat track fittings 	



Simple swingbolt for quick locking

**Due to the wide variety of vehicles and interior configurations, mounting of the Lightweight Docking Station Mount to the vehicle floor is the responsibility of the customer.

Testing
The CS300 has been tested to requirements that exceed the defined in US FAA Circular AC 135-14A (chapter 1, paragraph 1d-6).
The CS300 has been tested to applicable requirements of the following specifications: <ul style="list-style-type: none"> ■ EN 1789:1999 ■ RTCA/DO-160D ■ MIL-STD-810F for shock and vibration. ■ IEC 60601-1 : 1988 ■ IEC 60068-2-27 : 1987 ■ ECRI PB-296 892 test method AIII.3.1, 3.2.2, 3.3 Please refer to the CS300 Operating Instructions for more detailed description.



CS300 Accessory Storage Case

The CS300 UTS is available in different languages. Please contact your local Sales representative for details. All pumps include 1-year warranty. Extended warranty coverage is available.